



LAMPS & MORE

REFIT MODULE 10 IP44

Lamps and More 

- LED module ideal for most GU10/MR16 luminaires
- Easy replacement on existing projects
- High efficiency
- Available in four different beam angles
- Available with different dimming options flexible for any project requirement.
- L90/B10 50.000h
- 35DCM
- IP44 (face only)



LIGHTSOURCE BY
bridgelux

IP44



Model	LED Power	CCT*	CRI80, CRI90 LED Source		Beam Angle	Colour**	Dimming Option	Extra
			80 (80)	90 (90)				
REFIT MODULE <i>(REFIT M)</i>	10.3W (10)	2700K (27B)	1379lm	1138lm	18° (18)	White (WH)	Without Driver (00)	No Extras (00)
		3000K (30B)	1435lm	1180lm	24° (24)	Black (BL)	Non Dimmable (ND)	Emergency (E1)
		4000K (40B)	1479lm	1265lm	38° (38)		Analogue (1-10V) (A1)	
					60° (60)		DMX (DX)	
						DAI (DL)		
						Push Button (PB)		
						Phase Cut (PC)		
						Wireless*** (WL)		

* CCT: 3500K, 5000K, 6500K available upon request.

** Other RAL colours available upon request.

*** The wireless dimming option includes driver and Bluetooth dimming accessory.

Ordering Code Example: REFIT M10-308-80-24-WH-ND-00



- LED module ideal for most GU10/MR16 luminaires
- Easy replacement on existing projects
- High efficiency
- Available in four different beam angles
- Available with different dimming options flexible for any project requirement.
- L90/B10 50.000h
- 35DCM
- IP44 (face only)





Model	LED Power	CCT*	CRI80, CRI90 LED Source		Beam Angle	Colour**	Dimming Option	Extra
			80 (80)	90 (90)				
REFIT MODULE (REFIT M)	6.1W (6)	2700K (27B)	812lm	677lm	18° (18)	White (WH)	Without Driver (00)	No Extras (00)
		3000K (30B)	845lm	705lm	24° (24)	Black (BL)	Non Dimmable (ND)	Emergency (D1)
		4000K (40B)	879lm	733lm	34° (34)		Analogue (1-10V) (A1)	
			56° (56)			DMX (DX)		
						DALI (DL)		
							Push Button (PB)	
							Phase Cut (PC)	
							Wireless*** (WL)	

* CCT: 3500K, 5000K, 6500K available upon request.

** Other RAL colours available upon request.

*** The wireless dimming option includes driver and Bluetooth dimming accessory.

Ordering Code Example: REFIT M6-30B-80-24-WH-ND-00



REFIT WD 6 IP44

Lamps and More 

- LED module ideal for most GU10/MR16 luminaires
- Easy replacement on existing projects
- High efficiency
- Available in four different beam angles
- Available with dimming options flexible for different project requirements.
- L90B10 50,000h
- 3 SDCM
- IP44 (face only)



Warm Dimming
1800K to 3000K

LIGHTSOURCE BY
bridgelux 




Model	LED Power	CCT	C8195 LED Source	Beam Angle	Colour*	Dimming Option	Extra
95 (C5)							
REFIT MODULE WD <i>(REFIT M WD)</i>	6.1W (S)	1800K-3000K <i>(1830B)</i>	518lm	18° (18)	White (WH)	Analogue (1-10V) (A1)	No Extras (00)
				24° (24)	Black (BL)	DAI (DL)	Emergency (D1)
				34° (34)		Phase Cut (PC)	
				56° (56)		Wireless* (WL)	

* Other RAL colours available upon request.

** The wireless dimming option includes driver and Bluetooth dimming accessory.

Ordering Code Example: REFIT M WD6-1830B-95-24-WH-DL-00

Warm dimming 3000K to 1800K (6W)





Description	Lamp Holder	Watt	Voltage (50/60Hz)	CCT	CRI	Beam Angle	Luminous Flux	Shop Compatible
SORAA Brilliant HL 2700K /7,5W								
Soraa Brilliant HL	GU10	7.5W	220-240VAC	2700K	90	10°	620lm	YES
Soraa Brilliant HL	GU10	7.5W	220-240VAC	2700K	90	25°	650lm	NO
Soraa Brilliant HL	GU10	7.5W	220-240VAC	2700K	90	36°	650lm	NO
Soraa Brilliant HL	GU10	7.5W	220-240VAC	2700K	90	60°	650lm	NO
SORAA Brilliant HL 2700K /9,5W								
Soraa Brilliant HL	GU10	9.5W	220-240VAC	2700K	90	25°	720lm	NO
Soraa Brilliant HL	GU10	9.5W	220-240VAC	2700K	90	36°	720lm	NO
Soraa Brilliant HL	GU10	9.5W	220-240VAC	2700K	90	60°	720lm	NO
SORAA Brilliant HL 3000K /7,5W								
Soraa Brilliant HL	GU10	7.5W	220-240VAC	3000K	90	10°	640lm	YES
Soraa Brilliant HL	GU10	7.5W	220-240VAC	3000K	90	25°	660lm	NO
Soraa Brilliant HL	GU10	7.5W	220-240VAC	3000K	90	36°	660lm	NO
Soraa Brilliant HL	GU10	7.5W	220-240VAC	3000K	90	60°	660lm	NO
SORAA Brilliant HL 3000K /9,5W								
Soraa Brilliant HL	GU10	9.5W	220-240VAC	3000K	90	25°	730lm	NO
Soraa Brilliant HL	GU10	9.5W	220-240VAC	3000K	90	36°	730lm	NO
Soraa Brilliant HL	GU10	9.5W	220-240VAC	3000K	90	60°	730lm	NO

GU10 LED LAMPS

SORAA

Lamps and More 

BASED WITH
SORAA



Description	Lamp Holder	Watt	Voltage (50/60Hz)	CCT	CRI	Beam Angle	Luminous Flux	Snap Compatible
SORAA Vivid 2700K /7,5W								
Soraa Vivid	GU10	7.5W	220-240VAC	2700K	95	10°	390lm	YES
Soraa Vivid	GU10	7.5W	220-240VAC	2700K	95	25°	410lm	NO
Soraa Vivid	GU10	7.5W	220-240VAC	2700K	95	36°	410lm	NO
Soraa Vivid	GU10	7.5W	220-240VAC	2700K	95	60°	410lm	NO
SORAA Vivid 2700K /9,5W								
Soraa Vivid	GU10	9.5W	220-240VAC	2700K	95	25°	465lm	NO
Soraa Vivid	GU10	9.5W	220-240VAC	2700K	95	36°	465lm	NO
Soraa Vivid	GU10	9.5W	220-240VAC	2700K	95	60°	465lm	NO
SORAA Vivid 3000K /7,5W								
Soraa Vivid	GU10	7.5W	220-240VAC	3000K	95	10°	410lm	YES
Soraa Vivid	GU10	7.5W	220-240VAC	3000K	95	25°	435lm	NO
Soraa Vivid	GU10	7.5W	220-240VAC	3000K	95	36°	435lm	NO
Soraa Vivid	GU10	7.5W	220-240VAC	3000K	95	60°	435lm	NO
SORAA Vivid 3000K /9,5W								
Soraa Vivid	GU10	9.5W	220-240VAC	3000K	95	25°	490lm	NO
Soraa Vivid	GU10	9.5W	220-240VAC	3000K	95	36°	490lm	NO
Soraa Vivid	GU10	9.5W	220-240VAC	3000K	95	60°	490lm	NO
Soraa Vivid 4000K /7,5W								
Soraa Vivid	GU10	7.5W	220-240VAC	4000K	95	10°	430lm	YES
Soraa Vivid	GU10	7.5W	220-240VAC	4000K	95	25°	455lm	NO
Soraa Vivid	GU10	7.5W	220-240VAC	4000K	95	36°	455lm	NO
Soraa Vivid	GU10	7.5W	220-240VAC	4000K	95	60°	455lm	NO



Spreader Snap Accessory	Beam
Beam Spreader Snap	17°
Beam Spreader Snap	25°
Beam Spreader Snap	36°
Beam Spreader Snap	60°



Linear Snap Accessory	Beam
Linear Snap	10°-25°
Linear Snap	10°-36°
Linear Snap	10°-60°



Flat to Snap Accessory	Beam
Flat to Snap	25°-25°
Flat to Snap	36°-36°



Louver Snap Accessory	Cutoff Angle
Louver Snap	40°



Aimable Snap Accessory	
Aim Lens Snap	



CCT Shifter Snap Accessory	
CCT Shifter Snap	1/4
CCT Shifter Snap	1/2
CCT Shifter Snap	3/4



Clear Snap Accessory	
Clear Snap	Use this with Gel and Dichroic filter



Enhance Accessory	
Enhance	Color -enhancing filter to modify the spectrum of Soraa Vivid lamps



GU10 LED LAMPS SYLVANIA

Lamps and More 

SYLVANIA



Description	Lamp Holder	Watt	Voltage (50/60Hz)	CCT	CRI	Beam Angle	Luminous Flux
-------------	-------------	------	-------------------	-----	-----	------------	---------------

RefLED Superia Retro E550 Dimmable Supercolor

RefLED Retro Superia E550	GU10	5W	220-240VAC	2700K	90	36°	405lm
RefLED Retro Superia E550	GU10	5W	220-240VAC	3000K	90	36°	405lm
RefLED Retro Superia E550	GU10	5W	220-240VAC	3000K	90	36°	405lm

RefLED Superia Retro E550 Dimmable

RefLED Retro Superia E550	GU10	4.5W	220-240VAC	2700K	80	36°	345lm
RefLED Retro Superia E550	GU10	4.5W	220-240VAC	3000K	80	36°	345lm
RefLED Retro Superia E550	GU10	4.5W	220-240VAC	4000K	80	36°	360lm
RefLED Retro Superia E550	GU10	4.5W	220-240VAC	6500K	80	36°	360lm
RefLED Retro Superia E550	GU10	5W	220-240VAC	2700K	80	36°	450lm
RefLED Retro Superia E550	GU10	5W	220-240VAC	3000K	80	36°	450lm
RefLED Retro Superia E550	GU10	5W	220-240VAC	4000K	80	36°	475lm
RefLED Retro Superia E550	GU10	5W	220-240VAC	6500K	80	36°	475lm
RefLED Retro Superia E550	GU10	6W	220-240VAC	2700K	80	36°	550lm
RefLED Retro Superia E550	GU10	6W	220-240VAC	3000K	80	36°	550lm
RefLED Retro Superia E550	GU10	6W	220-240VAC	4000K	80	36°	580lm
RefLED Retro Superia E550	GU10	6W	220-240VAC	6500K	80	36°	580lm

RefLED Superia Retro E550

RefLED Retro Superia E550	GU10	4W	220-240VAC	2700K	80	36°	345lm
RefLED Retro Superia E550	GU10	4W	220-240VAC	3000K	80	36°	345lm
RefLED Retro Superia E550	GU10	4W	220-240VAC	4000K	80	36°	360lm
RefLED Retro Superia E550	GU10	4W	220-240VAC	6500K	80	36°	360lm
RefLED Retro Superia E550	GU10	5W	220-240VAC	2700K	80	36°	450lm
RefLED Retro Superia E550	GU10	5W	220-240VAC	3000K	80	36°	450lm
RefLED Retro Superia E550	GU10	5W	220-240VAC	4000K	80	36°	475lm
RefLED Retro Superia E550	GU10	5W	220-240VAC	6500K	80	36°	475lm
RefLED Retro Superia E550	GU10	6W	220-240VAC	2700K	80	36°	550lm
RefLED Retro Superia E550	GU10	6W	220-240VAC	3000K	80	36°	600lm
RefLED Retro Superia E550	GU10	6W	220-240VAC	4000K	80	36°	620lm
RefLED Retro Superia E550	GU10	6W	220-240VAC	6500K	80	36°	620lm
RefLED Retro Superia E550	GU10	7.3W	220-240VAC	2700K	80	36°	700lm
RefLED Retro Superia E550	GU10	7.3W	220-240VAC	3000K	80	36°	700lm
RefLED Retro Superia E550	GU10	7.3W	220-240VAC	4000K	80	36°	750lm
RefLED Retro Superia E550	GU10	7.3W	220-240VAC	6500K	80	36°	750lm



SYLVANIA

Description	Lamp Holder	Watt	Voltage	CCT	CRI	Beam Angle	Luminus Flux
-------------	-------------	------	---------	-----	-----	------------	--------------

RefLED Superia Retro MR16 Dimmable

RefLED Retro Superia MR16	GU5.3	4.4W	12V	2700K	80	36°	345lm
RefLED Retro Superia MR16	GU5.3	4.4W	12V	3000K	80	36°	345lm
RefLED Retro Superia MR16	GU5.3	4.4W	12V	4000K	80	36°	380lm
RefLED Retro Superia MR16	GU5.3	4.4W	12V	6500K	80	36°	380lm
RefLED Retro Superia MR16	GU5.3	5.8W	12V	2700K	80	36°	460lm
RefLED Retro Superia MR16	GU5.3	5.8W	12V	3000K	80	36°	460lm
RefLED Retro Superia MR16	GU5.3	5.8W	12V	4000K	80	36°	480lm
RefLED Retro Superia MR16	GU5.3	5.8W	12V	6500K	80	36°	480lm
RefLED Retro Superia MR16	GU5.3	7.5W	12V	2700K	80	36°	621lm
RefLED Retro Superia MR16	GU5.3	7.5W	12V	3000K	80	36°	621lm
RefLED Retro Superia MR16	GU5.3	7.5W	12V	4000K	80	36°	621lm
RefLED Retro Superia MR16	GU5.3	7.5W	12V	6500K	80	36°	621lm

RefLED Retro MR16

RefLED Retro MR16	GU5.3	4.3W	12V	2700K	80	36°	345lm
RefLED Retro MR16	GU5.3	4.3W	12V	3000K	80	36°	345lm
RefLED Retro MR16	GU5.3	4.3W	12V	4000K	80	36°	345lm
RefLED Retro MR16	GU5.3	4.3W	12V	6500K	80	36°	345lm
RefLED Retro MR16	GU5.3	4.6W	12V	3000K	80	36°	425lm
RefLED Retro MR16	GU5.3	4.6W	12V	4000K	80	36°	425lm
RefLED Retro MR16	GU5.3	4.6W	12V	6500K	80	36°	425lm
RefLED Retro MR16	GU5.3	6W	12V	3000K	80	36°	600lm
RefLED Retro MR16	GU5.3	6W	12V	4000K	80	36°	621lm
RefLED Retro MR16	GU5.3	6W	12V	6500K	80	36°	621lm

T8/T5 LED LAMPS SYLVANIA

Lamps and More 

SYLVANIA



Description	Lamp Holder	Watt	Voltage (50/60Hz)	CCT	CRI	Luminus Flux	Length	Lamp Finish
ToLEDo Superia T8 Universal								
ToLEDo Superia T8 Universal	G13	7.5W	220-240VAC	4000K	80	1100lm	60.4cm	Frosted
ToLEDo Superia T8 Universal	G13	16W	220-240VAC	4000K	80	2400lm	121.4cm	Frosted
ToLEDo Superia T8 Universal	G13	16W	220-240VAC	6500K	80	2400lm	121.4cm	Frosted
ToLEDo Superia T8 Universal	G13	23W	220-240VAC	4000K	80	3600lm	151.4cm	Frosted
ToLEDo Superia T8 Universal	G13	23W	220-240VAC	6500K	80	3600lm	151.4cm	Frosted
ToLEDo T8 Universal								
ToLEDo Superia T8	G13	18W	220-240VAC	4000K	80	2000lm	121.4cm	Frosted
ToLEDo Superia T8	G13	23W	220-240VAC	4000K	80	2800lm	151.4cm	Frosted
ToLEDo Superia T8 CCG & AC								
ToLEDo Superia T8 CCG & AC	G13	15W	220-240VAC	4000K	80	2550lm	121.2cm	Frosted
ToLEDo Superia T8 CCG & AC	G13	18W	220-240VAC	4000K	80	3100lm	121.2cm	Frosted
ToLEDo Superia T8 CCG & AC	G13	18W	220-240VAC	6500K	80	3100lm	121.2cm	Frosted
ToLEDo Superia T8 CCG & AC	G13	24W	220-240VAC	4000K	80	3700lm	151.3cm	Frosted
ToLEDo Superia T8 CCG & AC	G13	24W	220-240VAC	3000K	80	3850lm	151.3cm	Frosted
ToLEDo Superia T8 CCG & AC	G13	24W	220-240VAC	4000K	80	4100lm	151.3cm	Frosted
ToLEDo Superia T8 CCG & AC	G13	24W	220-240VAC	6500K	80	4100lm	151.3cm	Frosted
ToLEDo Superia T5 AC								
ToLEDo Superia T5 AC	G13	16W	220-240VAC	4000K	80	2400lm	114.9cm	Frosted
ToLEDo Superia T5 AC	G13	26W	220-240VAC	4000K	80	3900lm	114.9cm	Frosted
ToLEDo Superia T5 AC	G13	18.5W	220-240VAC	4000K	80	2800lm	144.9cm	Frosted
ToLEDo Superia T5 AC	G13	26W	220-240VAC	4000K	80	3900lm	144.9cm	Frosted



SYLVANIA

Description	Lamp Holder	Watt	Voltage	CCT	CRI	Luminous Flux	Finish
ToLEDo Retro GLS Dimmable							
ToLEDo RT GLS Dimmable	B22	7W	220-240VAC	2700K	80	806lm	Clear
ToLEDo RT GLS Dimmable	E27	7W	220-240VAC	2700K	80	806lm	Clear
ToLEDo RT GLS Dimmable	E27	11.2W	220-240VAC	2700K	80	1521lm	Clear
ToLEDo RT GLS Dimmable	E27	7W	220-240VAC	2700K	80	806lm	Satin
ToLEDo RT GLS Dimmable	E27	9W	220-240VAC	2700K	80	1055lm	Satin
ToLEDo RT GLS Dimmable	E27	9W	220-240VAC	4000K	80	1055lm	Satin
ToLEDo RT GLS Dimmable	E27	9W	220-240VAC	6500K	80	1055lm	Satin
ToLEDo RT GLS Dimmable	E27	11.2W	220-240VAC	2700K	80	1521lm	Satin
ToLEDo RT GLS Dimmable	B22	11.2W	220-240VAC	2700K	80	1521lm	Satin



ToLEDo Retro GLS

ToLEDo RT GLS	B22	4.5W	220-240VAC	2700K	80	470lm	Clear
ToLEDo RT GLS	E27	4.5W	220-240VAC	2700K	80	470lm	Clear
ToLEDo RT GLS	E27	4.5W	220-240VAC	4000K	80	470lm	Clear
ToLEDo RT GLS	E27	6W	220-240VAC	2700K	80	640lm	Clear
ToLEDo RT GLS	B22	7W	220-240VAC	2700K	80	806lm	Clear
ToLEDo RT GLS	E27	7W	220-240VAC	2700K	80	806lm	Clear
ToLEDo RT GLS	E27	7W	220-240VAC	4000K	80	806lm	Clear
ToLEDo RT GLS	E27	8W	220-240VAC	2700K	80	1055lm	Clear
ToLEDo RT GLS	E27	8W	220-240VAC	4000K	80	1055lm	Clear
ToLEDo RT GLS	E27	11W	220-240VAC	2700K	80	1521lm	Clear



ToLEDo Retro Candle Dimmable

ToLEDo RT Candle Dimmable	B22	4.5W	220-240VAC	2700K	80	470lm	Clear
ToLEDo RT Candle Dimmable	E14	4.5W	220-240VAC	2700K	80	470lm	Clear
ToLEDo RT Candle Dimmable	E27	4.5W	220-240VAC	2700K	80	470lm	Clear
ToLEDo RT Candle Dimmable	E14	4.5W	220-240VAC	2700K	80	470lm	Satin
ToLEDo RT Candle Dimmable	E14	4.5W	220-240VAC	4000K	80	470lm	Satin
ToLEDo RT Candle Dimmable	E14	4.5W	220-240VAC	6500K	80	470lm	Satin



ToLEDo Retro Candle

ToLEDo RT Candle	B22	2.5W	220-240VAC	2700K	80	250lm	Clear
ToLEDo RT Candle	E14	2.5W	220-240VAC	2700K	80	250lm	Clear
ToLEDo RT Candle	B22	4.5W	220-240VAC	2700K	80	470lm	Clear
ToLEDo RT Candle	E14	4.5W	220-240VAC	2700K	80	470lm	Clear
ToLEDo RT Candle	E27	4.5W	220-240VAC	2700K	80	470lm	Clear
ToLEDo RT Candle	E14	6W	220-240VAC	2700K	80	806lm	Clear
ToLEDo RT Candle	E27	6W	220-240VAC	2700K	80	806lm	Clear



HOMOGENEOUS 5VDC

Lamps and More 



Lighting management options:
DALI/DMX512/PHASE CUT/IR/RF/Bluetooth

Code	Description	No.LED	Colour	Lamp Holder	Watt	Voltage	Diameter	Beam Angle
LED.301 /CC	HOMOGENEOUS 5W	1	RGB	CABLE	5W	5VDC	51mm	45°

LED MODULE RGB


- LED Modules for illuminating advertising boards, company name and logo boards, etc.
- Ideal for backlighting plexiglass and other special constructions.
- Reduced maintenance costs.
- Bright, diffuse light and saturated colours.
- Outdoor installation IP65.
- Adhesive tape at the rear side of the module.
- SMD LEDs.
- Sold in chain of 20 pcs.

Lighting management options:
DALI/DMX512/PHASE CUT/IR/RF/Bluetooth



Code*	No.LED	Colour	Watt	Dimensions	Voltage	Beam Angle	IP
LEM.012 /CA	4 (pG8 in one chip)	RGB	1.3W	55x7x34mm	12VDC	120°	IP65

*Note: CA=Common Anode



- LED Modules for illuminating advertising boards, company name and logo boards, etc.
- ABS Casing and Aluminium PCB
- Screw hole on the PCB for durable installation
- Adhesive tape at the rear side of the module.
- Standard chain of 50 modules.


Lighting management options:

On-Off/DALI0..10V/1..10V/DMX512/PHASE CUT/R/R/RF/PUSH BUTTON/Bluetooth



Code	No.LED	Watt	Dimensions	CCT*	CRI	Luminus FLUX (LM)	Lumen Efficacy	Voltage	Beam Angle	IP
LEM.015	3	1.2W	76x1 6x6mm	2700K	CR180+	110 lm	91 lm/W	12VDC	120°	IP67
LEM.014	3	1.2W	76x1 6x6mm	3000K	CR180+	115 lm	95 lm/W	12VDC	120°	IP67
LEM.013	3	1.2W	76x1 6x6mm	4000K	CR180+	120 lm	100 lm/W	12VDC	120°	IP67
LEM.008	3	1.2W	76x1 6x6mm	5000K	CR180+	125 lm	104 lm/W	12VDC	120°	IP67

* Available also in 6000K upon request.



CHAIN WASH

LED Module 20°x70°

Lamps and More 

- ABS Casing and Aluminium PCB
- Screw hole on the PCB for durable installation
- LED Modules for illuminating advertising boards, company name and logo boards, etc.
- Adhesive tape of the rear side of the module.
- Standard chain of 21 LED modules (7 sets of 3 modules).
- Cutting every 3 LED modules (on indicative RED cable parts only).

Lighting management options:

On-Off/DALI(0...10V/1...10V)/DMX512/PHASE CUT/IR/RF/PUSH BUTTON/Bluetooth



Code	3-Module Chain	Watt	CCT	CRI	Voltage	Beam Angle	IP
LEM.020	3	3x2.7W	3000K	CR180	12VDC	20°x70°	IP65
LEM.021	3	3x2.7W	4000K	CR180	12VDC	20°x70°	IP65
LEM.022	3	3x2.7W	6500K	CR180	12VDC	20°x70°	IP65

